

History 1
 1.11.3.0 1
Add 1
Change 1
Debug 1
 1.11.2.0 1
 1.11.1.0 2
 1.11.0.0 3
 1.10.6.0 3
 1.10.5.0 4
 1.10.4.0 4
 1.10.3.0 4
 1.10.2.0 4
 1.10.1.0 5
 1.10.0.0 5
 1.9.3.9 5
 1.9.3.8 6
 1.9.3.7 6
 1.9.3.5 6
 1.9.3.4 6
 1.9.3.3 6
 1.9.3.2 7
 1.9.3.1 7
 1.9.3.0 7
 1.9.2.1 7
 1.9.2.0 8
 1.9.1.0 8
 1.9.0.0 9
 1.8.2.0 9
 1.8.1.1 9
 1.8.1.0 9
 1.8.0.0 10
 1.7.0.1 10
 1.7.0.0 10

History

1.11.3.0

Add

- DevList.Search Module 가
- SearchTextBox "Search" 가
- FormAIStatusCode : , Code가 0
- SdoAbortCodeDescription 가 : Shell LogViewer 가
- FormSetup.Form.AiPrecision Property 가
- Shell.Check 가
- ELMO Slot Driver
- FormFirmware.Reset MultiSelect
- NetState EscState
- Config.CheckMultiAxis

Change

- DcOffsetDefault
- 5001 Profile Step ID PhysAddr + 1 (: ID = PhysAddr)

Debug

- Disconnect Topology Update Topology
- DevList.Search :
- NetID 0 FormESC
- FormSlot Module ModIndent가 0 가
- NetState

1.11.2.0

-
- ControlLock 가
- AppSetup.t.formInfo.AlarmMonitor.DisplayAlarm Property 가
- Config.InPdoSkipCount Property 가
- AllowNodeNameChange Property 가¹⁾
- DeviceList.xml 가
- Config.DriverRawPDO
- AIState , Stop
- FormFirmware.Reset Device
- RemoteMode
-
- FormAI / FormAO Graph 가

- Dictionary enum
- TempController 0
- FormSetup 가
- Config
 - , 가
 - NetInfo.LogicIn / NetInfo.LogicOut Servo 가
 - Scan / Download Exception
 - IO Scan/Download 1 Dock
 - Download BackupFile Exception
- Shell
- Master-Slave
- GetModulInfos Exception 2)

1.11.1.0

- App
- Dock Expert
- 5001 Profile IO
- FormDevList
 - ExpandOne, ExpandAll, CollapseOne, CollapseAll 가
 - SearchNodeWithChannelName 가
 - DeviceName 가
- MotorMonitor : ColumnCount Property 가
- FormDIO
 - RootColumnCount Prop가르ty 가 : DIO Form ColumnCount
 - ColumnCount_1 Enum 가
- FormAI / FormAO : Precision
- Setup
 - AppSetup.Form.DeviceList.InitTreeLevel Property 가
 - AutoLoa .NameOnly Property 가
- Config
 - TopologyView : Port line
 - Module Append
 - DefaultZoom
 - ProfileNo 3)
 - UpdateForm : Event
 - ID / ID , TreeView
 - MultiAxis ID 가4)
 - TopologyView AIState 5)
 - DI / DO StartCh 가
 - SM / FMMU 6)
 - DioMap, AioMap Leak
 - IsRevisionNoNotMatchAnError Property가 false , RevisionNoNotMatch
 - Net , TopologyView Update
 - CustomIoMap : Map 가
 - MDP type Object-DataType Matching 7)
 - Object DataType Size가 , Object DataSize

- InfoRefFilePath Node
- ServoTunes
 - ServoTunes
 - LoadOne
- AlarmMonitor 가 : Axis Alarm, Slave CommError
- EtherCAT
 - MailBox Abort ⁸⁾ AbortCode log 가
 - Device가 ID가 0 가 AlarmMonitor
 - AlarmState Property 가 : AIState가 AlarmState AlarmMonitor

1.11.0.0

- SlaveCfg : ProfileNo 가
- 402 Profile Address
 - 402 Profile 64 .
 - , INVALID_ADDRESS_IN_402 ConfigError
- ConfigError 가 ()
- formConfig Leak
- ProfileNo.5003
- ServoTunes Data Read Error
- UsingStationAddress Property 가
 - CSA
- FormConfig.TopologyView
 - AIStatus 가
 - Group AIStatus
- Config.BaseAIState Property 가
- DcOffsetDefaultValue 가
- Firmware Reset : Main → Firmware

1.10.6.0

- EtherCAT
 - **DLL Logger** **AppDown**
 - Dictionary Search 가
 - DataType Object bit 가 가
 - TempController 가
 - Scan ecCfg_SetSlaveConfig : PreOP
 - ESI SM Enable Enable
- cEIP
 - cEIP AppDown
 - cEIP Version Parsing
 - cEIP MotorState Update failed

- NEMO
 - FW, Lib Version read failed

1.10.5.0

- SoftEtherCAT 가
 - ESC, SlaveRW
- EtherCAT Config
 - FMMU Section : Servo Sect
 - EBus_2 + Mii_2 Type Matching
 - ProcessData Entry Type ETC 가
- DO Repeat RepeatCount 가 0 ,

1.10.4.0

- IO Form Dock 가
- Setup : FormIO HideMenu Property 가

1.10.3.0

- Config
 - TopologyView : PortMonitoring Option 가
 - NetInfo : DcOffset : %
- Dictionary : Enum
- ⁹⁾ 가
- EtherCAT : OPMODE_PT 가

1.10.2.0

- FormConfig : Slave AutoReset 가
- FormPDO : 2 ~ 7 bit size Data 가

1.9.3.8

- EtherCAT Lib

1.9.3.7

- Shell
 - API ,
- EtherCAT
 - Firmware Upload UI
 - ETS-MC02P, CMC HomeReturn

1.9.3.5

- DeviceList
 - EtherCAT (Driver) : MajorNo.MinorNo.BuildNo.RevNo

1.9.3.4

- DeviceList
 - EtherCAT : MajorNo.MinorNo.BuildNo.RevNo
 - EtherCAT Version Compare

1.9.3.3

- HomeReturn
 - HomeReturn , MotorMonitor / AxisList

1.9.3.2

- ServoTunes
 - Nikki Denso : Nikki Denso 가 , Exception Error
 - Servo가 Net ServoTunes

1.9.3.1

- EtherCAT InitAlState DontChange , PDO
- Slave SDO Read
- ServoTunes EEPROM Write 가

1.9.3.0

- EtherCAT Version : File → GetVerInfo
- AutoSaveEnable, AutoSavePath 가
- AutoLoadEnable, AutoLoadPath 가
- FirmUp : 0 State가
- DO Custom Channel Control : Setup
- LX554 48 : LX554 → LX554(48)
- LX553 : LX553 → LX552(40)

1.9.2.1

- EtherCAT HomeReturn Success
- UnknownESC Register Read (DIStatus)
 - TopologyView, ESC Viewer Update
 - 1.9.2.0 YASKAWA Driver Topology가

1.9.2.0

- ESC Viewer
 - PortControl 가
 - UI
 - ESC Type Register Read/Wrtie
- TopologyView
 - ESC Redundancy Check
 - Port Open ESC
- DSP Viewer
 - FW 2.66 EEclnfoID 가 (SendCount, ReceiveCount)
 - Read Checkbox 가
- DeviceList
 - EtherCAT VersionCheck

1.9.1.0

- ServoTunes
 - UI
 - Write One-All, Write All-All
- Config
 - TopologyView
 - SlaveTree
 - Coupler - Coupler / Hub - Hub
 - PortOpen
 - SlaveInfo DcInfo 가
 - OHT_Step 가
 - 402 Profile Axis Info Update
 - Scan
 - Master Redundancy
- FormIO
 - EtherCAT IO Form Title NetID 가
 - EtherCAT AI / AO Aio Mode
 - DIO GetMulti Selction 가 (GetMulti / GetOne)
 - LX534 + 64 IO , SDK 32
- DeviceList
 - EtherCAT Slot 10 , Sorting
 - 1,10,11,2,3,4 1,2,3,4,10,11
- Dictionary

- , UI
- Shell
 - ToHex(),ToDec(),ToBit() 가
- FirmUp
 - DeviceNode DeviceInfo Update

1.9.0.0

- Config DC-Sync Factor (OP)

1.8.2.0

- Dictionary : EnumType null
 -
- AI / AO Form : Multi-Channel Name Copy/Paste
- SevoTunes : SanyoDenki, NikkiDenso

1.8.1.1

- SlaveRW : SDO Read Sign/UnSign
- DevList Form : PulseType
- Config : 402Profile DcSyncMode가 가

1.8.1.0

- CMC Axis 가
- EtherCAT FW Version 1.60 DCSyncEnable

1.8.0.0

- EtherCAT DcSyncEnable 1, 2 가
- Dictionary : EnumType Text
- SDP Type Visible 가
- 가 Log Skip
- ServoTunes : Yaskawa EtherCAT

1.7.0.1

- Setup Form MinorBugFix
- Setup Form NEMO ELP Logic

1.7.0.0

- EtherCAT ReserseConnetionCheck MinorBugFix
- EtherCAT Multi-Device FirmwareUpdate
- EtherCAT Virtual Module Append MinorBugFix

1)

false DevList Node 가

2)

Invisible Node 가

3)

가 900

4)

ID ID

5)

AIState 가

6)

Config SetFMMU() , Scan Get

7)

Dictionary WeiduMuiller Object가

8)

CoeSDO Read Fail / write Fail

9) 10)

,

PlatformInfo.xml, DeviceList.xml

From:

<https://www.comizoa.com/info/> - -

Permanent link:

https://www.comizoa.com/info/doku.php?id=application:comiide:20_intro:10_history&rev=1713945136

Last update: **2024/07/08 18:23**