

Table of Contents

Case 1	1
AddInfo	1
Cause	1
Solution	1

Unknown Slave

× SCAN 결과 알 수 없는 Slave가 확인됨

Case 1

AddInfo

The screenshot shows the 'Configurator' software interface. At the top, there are buttons for 'Scan', 'Download', 'Upload', 'Save', 'Load', and 'Close'. Below these are tabs for 'Topology', 'Net Info', 'Slave Info', and 'ProcessData'. The 'Topology' tab is active, showing a network diagram with a master node '[0200] Master MASTER-DC' and three slave nodes: '[0001] NONE Unknown', '[0002] NONE Unknown', and '[0003] NONE Unknown'. A red box highlights the 'Net Info' section, which lists three entries: '[0000h] Unknown', '[0000h] Unknown', and '[0000h] Unknown'. At the bottom, there are buttons for 'Index', 'Addr', 'Initial', 'PreOP', 'SafeOP', and 'OP', along with a 'Apply AutoAddress To Servo' button and '+' '-' controls.

Cause

- SCAN 시 참조할 ESI File(*.xml) 이 없음

Solution

- XML 폴더 (.\ComiIDE\Data\XML) 에 Unknown으로 확인되는 Slave의 XML 파일을 복사¹⁾

1)

ECatConfig 사용 시 .\EcatConfig\Data\XML

From:

<https://www.comizoa.com/info/> - -

Permanent link:

https://www.comizoa.com/info/doku.php?id=platform:ethercat:1_setup:10_config:ts:unknown_slave&rev=1540445653

Last update: **2024/07/08 18:22**