

Table of Contents

Case 1	1
AddInfo	1
Cause	1
Solution	1

ethercat, 이더넷, panasonic, 파나소닉, unknown, config, 실패, scan

Unknown Slave

× SCAN 결과 알 수 없는 Slave가 확인됨

Case 1

AddInfo

The screenshot shows the 'Configurator' software interface. At the top, there are buttons for 'Scan', 'Download', 'Upload', 'Save', 'Load', and 'Close'. Below these are tabs for 'Topology', 'Net Info', 'Slave Info', and 'ProcessData'. The 'Topology' tab is active, showing a network diagram with four nodes: a Master node labeled '[0200] Master MASTER-DC' and three Slave nodes labeled '[0001] NONE Unknown', '[0002] NONE Unknown', and '[0003] NONE Unknown'. A red box highlights the 'Topology' tab and the list of nodes on the left, which includes '[0000h] Unknown' and '[0000h] Unknown'. At the bottom, there are buttons for 'Index', 'Addr', 'Initial', 'PreOP', 'SafeOP', and 'OP', along with a '+ -' button and a button labeled 'Apply AutoAddress To Servo'.

Cause

- SCAN 시 참조할 ESI File(*.xml) 이 없음

Solution

- XML 폴더 (.\ComiIDE\Data\XML) 에 Unknown으로 확인되는 Slave의 XML 파일을 복사 ¹⁾

Category

1)

ECatConfig 사용 시 .\EcatConfig\Data\XML

From:

<https://www.comizoa.com/info/> - -

Permanent link:

https://www.comizoa.com/info/doku.php?id=platform:ethercat:1_setup:10_config:ts:unknown_slave&rev=1540520552

Last update: **2024/07/08 18:22**